



 >Router1>CLI

% Invalid input detected at '^' marker.

```
zeeshan(config-line)#password 14598
zeeshan(config-line)#login
zeeshan(config-line)#exit
zeeshan(config)#line vty 0 4
zeeshan(config-line)#password 14598
zeeshan(config-line)#login
zeeshan(config-line)#exit
zeeshan(config)#
```

to fill entire screen



>Router1>CLI

User Access Verification

Password:

zeeshan>enable

zeeshan#configure

Configuring from terminal, memory, or network [terminal]? terminal

Enter configuration commands, one per line. End with CNTL/Z.

zeeshan(config)#enable secret password

zeeshan(config)#exit

zeeshan#

to fill entire screen



```
zeeshan(config)#banner motd #NO ACCESS  
Enter TEXT message. End with the character '#'.
```

```
enable
```

```
exit
```

```
#
```

```
zeeshan(config)#banner motd # NO ACCESS#  
zeeshan(config)#
```

to fill entire screen





% Invalid input detected at '^' marker.

```
zeeshan(config)#int
zeeshan(config)#interface f0
zeeshan(config)#interface f0/
zeeshan(config)#interface f0/0
zeeshan(config-if)#ip add
zeeshan(config-if)#ip address 192.168.1.1 255.255.255.0
zeeshan(config-if)#no shut
```

to fill entire screen





```
zeeshan#  
zeeshan#  
zeeshan#  
zeeshan#  
zeeshan#  
zeeshan#  
zeeshan#  
zeeshan#  
zeeshan#  
zeeshan#write  
Building configuration...  
[OK]  
zeeshan#
```

to fill entire screen





```
Router(config)#hostname zeeshan alam
                        ^
% Invalid input detected at '^' marker.

Router(config)#h9st
                    ^
% Invalid input detected at '^' marker.

Router(config)#
Router(config)#hostname zeeshan
```

to fill entire screen

