

NAME :- ASAD KHAN

ID :- 14944

Department :- B.S. Cs

Semester :- 4th

Assignment :- 3rd

Subject :- Computer

Q1 Give answer to each of the following?

A. Discuss the two approaches for dealing with multiple interrupts?

Ans:- 1. The first is to disable interrupts while an interrupt is being processed. A disabled interrupt simply means that the processor can and will ignore that interrupt request signal. The drawback to the preceding approach is that it does not take into account relative priority or time-critical needs.

2. A second approach is to define priorities for interrupts and to allow an interrupt of higher priority to cause a lower-priority interrupt handler to be itself interrupted.

B. Discuss the types of exchanges that are needed by indicating the major forms of input and output for processor memory and IO modules?

Ans:- The types of exchanges that are needed by indicating the major forms of input and output for processor memory and IO modules are.

- Memory to processor :-

The processor reads an instruction or a unit of data from memory.

- Processor to Memory :-

The processor writes a unit of data to memory.

- IO to processor :-

The processor reads data from an IO device via an IO module.

NAME:- ASAD KHAN

ID:- 14944

Page No:- 02

• Processor to IO:-

The processor sends data to the IO device.

• IO to or from memory:-

For these two cases an IO module is allowed to exchange data directly with memory without going through the processor using direct memory access.

C. Discuss the Quickpath interconnect (QPI) protocol layers?

Ans:- QPI protocol layer. In this layer the packet is defined as the unit of transfer. One key function performed at this level is a Cache Coherency protocol which deals with making sure that main memory values held in multiple caches are consistent. A typical data packet payload is a block of data being sent to or from a cache.

D. Discuss the physical and logical architecture of PCIe in detail?

Ans:- Physical and logical Architecture of PCIe
→ A Root Complex device also referred to as a chipset or a host bridge connects the processor and memory subsystem to the PCI express switch fabric comprising one or more PCIe and PCIe Switch devices.

→ PCIe links from the chipset may attach to the following kinds of devices that

implement PCIe:

- Switch:- The Switch manages multiple PCIe Streams.
- PCIe endpoint:- An IO device or Controller that implements PCIe such as a Gigabit ethernet switch a graphics or video Controller disk interface or a Communications Controller.
- Legacy endpoint:- legacy endpoint category is intended for existing designs that have been migrated to PCIe express and it allows legacy behaviors such as use of IO space and locked transactions.
- PCIe/PCI bridges:- allows older PCI devices to be connected to PCIe-based systems.

Q² Write short note on each of the following:-

- wing :-

Ans:- A. Instruction Cycle:-

The processing required for a single instruction is called an Instruction Cycle. Using the simplified two step description given previously the instruction cycle is depicted the two steps are referred to as the fetch cycle and the execute cycle. Program execution halts only if the machine is turned off. Some sort of unrecoverable error occurs or a program instruction that halts the computer is encountered.

NAME:- ASAD KHAN

IDS-14944

Page No:- 04

Q. Instruction cycle state diagram:-
Ans:- The states in instruction cycle can be described as follows.

→ Instruction address Calculation (Iac)
Determine the address of the next instruction to be executed. Usually this involves adding a fixed number to the address of the previous instruction.

→ Instruction fetch (If):-
Read instruction from its memory location into the processor.

→ Instruction operation decoding (Iod):-
Analyze instruction to determine type of operation to be performed and operands to be used.

→ Operand address Calculation (Oac):-
The operation involves reference to an operand in memory or available via IO then determine the address of the operand.

→ Operand fetch (Of):-
Fetch the operand from memory or read it in from IO.

→ Data Operation (Do):-
Perform the operation indicated in the instruction.

→ Operand Store (Os):-
Write the result into memory or out to IO.

C. Classes of Interrupts:-

Ans:-

i. Program :-

It is generated by some condition that occurs as a result of an instruction execution such as arithmetic overflow division by zero attempt to execute an illegal machine instruction or reference outside a user's allowed memory space.

ii. IO :-

It is generated by an IO controller to signal normal completion of an operation request service from the processor or to signal a variety of error conditions.

iii. Time :-

It is generated by a time within the processor this allows the operating system to perform certain functions on a regular basis.

iv. Hardware failure :-

It is generated by a failure such as power failure or memory parity error.

D. Bus Interconnection Scheme:-

Ans:- The most common computer interconnection structures are based on the use of one or more system buses.

A system bus consists typically of from about fifty to hundreds of separate lines the lines can be classified into three functional groups:-

NAME: ASAD KHAN

ID: 14944

Page No: 06

a) Data lines:-

The data lines provide a path for moving data among system modules. These lines collectively are called the data lines bus.

b) Address lines:-

The Address lines are used to designate the source or destination of the data on the data bus.

The width of the address bus determines the maximum possible memory capacity of the system.

c) Control lines:-

The Control lines are used to control the access to and the use of the data and address lines. Because the data and address lines are shared by all components there must be a means of controlling their use. Typical control lines include memory write, memory read, IO write, IO read, Transfer Ack, Bus request, Bus grant, interrupt request, interrupt Ack, Clock and Reset.

Q³ Differentiate each of the following:-
A. Programming in hardware and programming in software.

* Programming in Hardware:-

The "program" is in the form of hardware and is termed a hard-

-ware Program. Suppose we Construct a general-purpose Configuration of arithmetic and logic function. This set of hardware will perform various function on data depending on Control Signals applied to the hardware. In the Original Case of customized hardware the system accepts data and produces results.

* Programming in Software :-

The new method of programming which is a sequence of codes or instructions is called Software programming.

In this method programming is much easier instead of sewing the hardware for each new program all we need to do is provide a new sequence of codes each code is in effect an instruction and part of the hardware interprets each instruction and generates Control Signals.

B. Program flow of Control without interrupt and with interrupt :-

- Ans :- *
- * In the interrupt cycle the processor checks to see if any interrupts have occurred indicated by the presence of an interrupt signal.
 - * If no interrupts are pending the processor proceeds to the fetch cycle and fetches the next instruction of the current program.

NAME:- ASAD KHAN

ID:- 14944

Page No:- 08

C. Disabled interrupt and nested interrupt processing:-

Ans:-

Disabled Interrupt:-

A disabled interrupt simply means that the processor can be and will ignore that interrupt request signal if an interrupt occurs during this time it generally remains pending and will be checked by the processor after the processor has enabled interrupts.

Nested Interrupt:-

A nested interrupt is to allow an interrupt of higher priority to cause a lower priority interrupt. A user program begins at $t=0$. At $t=10$, a printer interrupt occurs user information is placed on the system stack and execution continues at the printer interrupt service routine (ISR) while this routine is still executing at $t=15$ a communications interrupt occurs.

Q Solve each of the following:-

A. The hypothetical machine of has two I/O instructions. See figure 01:-
0011 = load AC from I/O
0111 = Store AC to I/O
In this cases the 12-bit address

Identifies a particular IO device. Show the program execution using the format of figure 3.5 for the following program:

Load AC from device 5.
Add Contents of memory location 940.
Store AC to device 6.

Assume that the next value retrieved from device 5 is 3 and that location 940 contains a value of 2.

Ans:- Memory (contents in hex): 300: 3005; 301: 5940; 302: 7006
Step 1: 3005 → IR; Step 2: 3 → AC
Step 3: 5940 → IR; Step 4: 3 + 2 = 5 → AC
Step 5: 7006 → IR; Step 6: AC → Device 6.

B. The program execution of figure 02 is described in the text using six steps expand this description to show the use of the MAR and MBR?

Ans:- 1. a. The PC contains 300 the address of the first instruction. This value is loaded into the MAR. b. The value in location 300 which is the instruction with the value 1940 in hexadecimal is loaded into the MBR and the PC is incremented. These two steps can be done in parallel. c. The value in the MBR is loaded into the IR.

2. a. The address portion of the IR (940) is loaded into the MAR. b. The value in location 940 is loaded into the MBR.

NAME: ASAD KHAN

ID: 14944

Page Nos: 10

c. The value in the MBR is loaded into the AC.

3. a. The value in the Pc (301) is loaded into the MAR. b. The value in location 301 which is the instruction with the value 5941 is loaded into the MBR and the Pc is incremented. c. The value in the MBR is loaded into the IR.

4. a. The address portion of the IR (941) is loaded into the MAR. b. The value in location 941 is loaded into the MBR. c. The old value of the AC and the value of location MBR are added and the result is stored in the AC.

5. a. The value in the Pc (302) is loaded into the MAR. b. The value in location 302 which is the instruction with the value 2941 is loaded into the MBR and the Pc is incremented. c. The value in the MBR is loaded into the IR.

6. a. The address portion of the IR (941) is loaded into the MAR. b. The value in the AC is loaded into the MBR. c. The value in the MBR is stored in location 941.

- C.
- what is the maximum directly addressable memory capacity in bytes?
 - Discuss the impact on the system speed if the microprocessor bus has:
 - 32-bit local address bus and a 16-bit local data bus, or
 - 16-bit local address bus and a 16-bit local data bus.
 - How many bits are needed for the program counter and the instruction register?

Ans: a. $2^{24} = 16 \text{ MB Bytes}$.

b. (1) if the local address bus is 32 bits the whole address can be transferred at once and decoded in memory however because the data bus is only 16 bits it will require 2 cycles to fetch a 32-bit instruction or operand.

(2) The 16-bits of the address placed on the address bus can't access the whole memory. thus a more complex memory interface control is needed to latch the first part of the address and then the second part.

c. The program counter must be at least 24 bits. typically a 32-bit microprocessor will have a 32-bit external address bus and a 32-bit program counter unless on-chip segment registers are used that may work with a smaller program counter.

NAME:- ASAD KHAN

ID:- 14944

Page No:- 12

If the instruction register is to contain the whole instruction it will have to be 32-bits long if it will contain only the op code called the op code register then it will have to be 8 bits long.

D.

Ans:- Clock Cycle =
 $1 = 125 \text{ ns}$ 8 MHz Bus Cycle = $4 \times 125 \text{ ns} = 500 \text{ ns}$
2 bytes transferred every 500 ns; thus transfer rate. 4 MBytes/sec.

Doubling the frequency may mean adopting a new chip manufacturing technology assuming each instructions will have the same number of clock cycles doubling the external data bus means wider maybe newer on chip data bus drivers latches and modifications to the bus control logic in the first case the speed of the memory chips will also need to double roughly not to slow down the microprocessor in the second case the "wordlength" of the memory will have to double to be able to send receive 32-bit quantities.

E.

Ans:- a. During a single bus cycle the 8-bit microprocessor transfers one byte while the 16-bit microprocessor transfers two bytes. The 16-bit microprocessor has twice

the data transfer rate.

b. Suppose we do 100 transfers of operands and instructions of which 50 are one byte long and 50 are two bytes long. The 8-bit microprocessor takes $50 + (2 \times 16 - 50) = 150$ bus cycle for the transfer. The 16-bit microprocessor requires $50 + 50 = 100$ bus cycles. Thus the data transfer rates differ by a factor of 1.5.

F.

Ans:- A bus cycle takes $0.25 \mu s$, so a memory cycle takes $1 \mu s$. If both operands are even aligned, it takes $2 \mu s$ to fetch the two operands. If one is odd-aligned, the time required is $3 \mu s$. If both are odd-aligned, the time required is $4 \mu s$.

G.

Ans:- Consider a mix of 100 instructions and operands on average they consist of 20% 32-bit items, 40% 16-bit items and 40% 8-bit items. The number of bus cycles required for the 16-bit microprocessor is $(2 \times 20) + 40 + 40 = 120$ for the 32-bit microprocessor the number required is 100. This amounts to an improvement of $20/120$ or about 17%.